



Medical and Health Facility Fire Protection

CARBON DIOXIDE is discharged as a white cloud of "snow" which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

UL Rated: 5B:C

Model: 322NM



5 YEAR WARRANTY

Rust free aluminum cylinders - up to 30% lighter than steel cylinders

Durable High Gloss Polyester Powder Paint

Antiseptic white paint finish (easy to clean)

All Metal Valve Construction

Independently tested to 11.7 TESLA and approved

QR Coded Bilingual Labels (English and Spanish)

AGENT TYPE	CARBON DIOXIDE
VALVE TYPE	CHROME PLATED BRASS
DESIGN	HORN
MODEL NUMBER	322NM
UL RATING	5B:C
CAPACITY (LBS.)	5
SHIPPING WT. (LBS.)	14
HEIGHT (IN.)	17.75
WIDTH (IN.)	8.25
DEPTH (IN.)	5.25
RANGE (INITIAL- FT)	3-8
DISCHARGE TIME (SEC.)	10
INCLUDED BRACKET	NM WALL

MR CONDITIONAL
 THIS EXTINGUISHER HAS BEEN TESTED TO OPERATE PROPERLY AND POSE NO SAFETY HAZARD IN AN MRI ENVIRONMENT ASSOCIATED WITH MR SYSTEMS OPERATING AT 11.7 TESLA OR LESS.



NON-MAGNETIC CONSTRUCTION - MR CONDITIONAL

WATER MIST is the ultimate extinguisher for Class A fires and where a potential Class C (electrical) hazard exists. The fine spray from the unique misting nozzle provides safety from electrical shock, greatly enhances cooling and soaking characteristics of the agent and reduces scattering of burning materials. The Amerex Water Mist extinguishers utilize de-ionized water making them the best extinguishers for protection of hospital environments, valuable books and documents, telecommunication facilities and "clean room" manufacturing facilities. The Amerex Water Mist extinguishers are easy to use, maintain, and service.

5 YEAR WARRANTY

RUGGED

Stainless Steel Cylinders
Durable High Gloss Polyester Powder Paint
Antiseptic white paint finish (easy to clean)
All Metal Valve Construction
Exclusive crevice free, butt welded cylinder

ENVIRONMENTALLY FRIENDLY

Independently tested to 11.7 TESLA and approved
Uses nitrogen, de-ionized water

CLEAN

Causes no respiratory problems
De-ionized water extinguishing agent (sold separately)
No powder residue

USER FRIENDLY

Wand provides greatest operator safety
Maximum visibility during discharge
No Class A and Class C rated
No thermal or static shock
Minimal training - simplest to use
De-ionized water - most economical agent available
QR coded labels (English and Spanish)

UL Rated: 2A:C

Models: B272
B270



AGENT TYPE	DE-IONIZED WATER	
DESIGN	HOSE & WAND	
MODEL NUMBER	B270NM	B272NM
UL RATING	2A:C	2A:C
CAPACITY	1.75 GAL	2.5 GAL
SHIPPING WT. (LBS. EMPTY)	7	8
HEIGHT (IN.)	19	24.5
HEIGHT WITH HOSE AND WAND INSTALLED (IN.)	24.5	27.5
WIDTH (IN.)	11	11
DEPTH (IN.)	7	7
RANGE (INITIAL- FT)	10-12	10-12
DISCHARGE TIME (SEC.)	72	80
NON-MAGNETIC WALL HOOK	YES	YES

MR CONDITIONAL
 THIS EXTINGUISHER HAS BEEN TESTED TO OPERATE PROPERLY AND POSE NO SAFETY HAZARD IN AN MRI ENVIRONMENT ASSOCIATED WITH MR SYSTEMS OPERATING AT 11.7 TESLA OR LESS.




Amerex Corporation

P.O. Box 81 ♦ Trussville, AL 35173
Ph: (205) 655-3271 ♦ Fax: 1-800-654-5980
sales@amerex-fire.com
www.amerex-fire.com

SL-900 3/2019