



Quality is Behind the Diamond

RUGGED

- 6 Year Warranty
- Stored Pressure Design
- Dependable Drawn Steel Cylinders
- Hydrographic Dip Process with Clear Coat Finish
- All Metal Valve Construction
 - Anodized Aluminum Valve Body
 - Anodized Aluminum Handle & Lever
- Temperature Range -65°F to 120°F

USER FRIENDLY

- Easy and Economical to Maintain and Service
- Large Loop Pull Pin
- Bar Coded and Bi-lingual Labels

OPTION

- USCG Approved with Bracket Listed on UL Label



**MODEL B417T
EVO™**

**MODEL B417T
MUDDY GIRL™**

ABC or Multi-Purpose extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F and coats surface to which it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

| AGENT TYPE | ABC DRY CHEMICAL | |
|-----------------------|-------------------|-------------------|
| VALVE TYPE | ANODIZED ALUMINUM | ANODIZED ALUMINUM |
| DESIGN | NOZZLE | NOZZLE |
| MODEL NUMBER | B417T EVO™ | B417T MUDDY GIRL™ |
| PART NUMBER | 25224 | 25153 |
| UL & ULC RATING | 1A:10B:C | 1A:10B:C |
| CAPACITY (LBS.) | 2.5 | 2.5 |
| SHIPPING WT. (LBS.) | 5.25/5.5 | 5.25/5.5 |
| HEIGHT (IN.) | 15.5 | 15.5 |
| WIDTH (IN.) | 5.75 | 5.75 |
| DEPTH (IN.) | 3 | 3 |
| RANGE (INITIAL - FT) | 9-15 | 9-15 |
| DISCHARGE TIME (SEC.) | 10 | 10 |
| INCLUDED BRACKET | WALL/VEHICLE | WALL/VEHICLE |