



Amerex Corporation



Model 600K 150 LB. HALON 1211 WHEELED FIRE EXTINGUISHER



- Brass, chrome plated operating valve
- 200 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Quick release 50 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyurethane paint finish
- Large color coded mylar instruction labels
- Operating temperature range: -65° to +120° F.
- 1 year limited warranty

SPECIFICATIONS	HALON 1211
MODEL NUMBER	600
AGENT TYPE	Halon 1211
CAPACITY (LBS.)	150
SHIPPING WEIGHT (LBS.) EMPTY / FULL	205 / 355
DISCHARGE TIME (SEC.)	48
CYLINDER - DOT 4BW240	
OPERATING PRESSURE (PSI)	200
TEST PRESSURE (PSI)	480
BURST PRESSURE (MINIMUM - PSI)	960
DISCHARGE RANGE (FT.)	30 - 40
TEMPERATURE RANGE (F)	-65 to 120
DISCHARGE RANGE (FT.)	30
SAFETY DISC BURST RANGE (PSI)	400 - 500
HOSE LENGTH (FT.)	50
HOSE DIAMETER (IN.)	.75
WHEELS (IN.) (SEE NOTE BELOW)	16 x 4
HEIGHT (IN.)	59
WIDTH (IN.)	29
DEPTH (IN.)	42

NOTE: Specify pneumatic or semi-pneumatic wheels

AMEREX CORPORATION

P.O. BOX 81 ❖ TRUSSVILLE, AL 35173-0081
Phone: (205) 655-3271 ❖ Fax: 1-800-654-5980
sales@amerex-fire.com ❖ www.amerex-fire.com